



**WATER-
COOLED**

Model 520030
DC Line
Load Resistor

The OMEGALINE® 5200 Series are extraordinary water terminations for DC applications or very low frequencies that exhibit excellent and stable RF characteristics during their full range of operating power. The rugged, precision-designed configuration of the 5200 Series provides reliability, serviceability, convenience and economy well suited for today's modern RF application.

FEATURES:

- RF power is dissipated in a proven, ceramic, rugged, film-type cylindrical resistor
- Potable water in open or closed systems
- Aluminum construction
- No field adjustments needed
- Non-contaminating water circuit

SPECIFICATIONS

POWER RATING (CONTINUOUS DUTY)	30 KW
EFFECTIVE FREQUENCY RANGE	DC
IMPEDANCE	25Ω nominal (others available)
WATER FLOW	20 GPM Minimum
WATER CONNECTORS	1- 1/4" x 11-1/2" NPT
INPUT CONNECTORS	Threaded terminals
NOMINAL DIMENSIONS	32.34" x 22.6" x 9.53"
NOMINAL WEIGHT	63 lbs.

Model 520030



ALTRONIC RESEARCH INC.

CALL TOLL FREE 1-800-482-LOAD

P.O. BOX 249, Yellville, AR 72687 (870) 449-4093

www.altronic.com

