



*Self-  
Contained*

## Model 5805 Heat Exchanger Resistor Load

The OMEGALINE® 5800 Series combines the performance of the water-cooled load with the quiet blower design of the air-cooled series to provide terminations for 50-ohm coaxial transmission lines. Power is dissipated in a reliable water-cooled load maintaining excellent and stable RF characteristics while the water is circulated through the internal cooling system. Manufacturers of transmitters, microwave components and power tubes as well as transmitting stations can be assured of ideal dummy load conditions during designing, testing, adjusting and aligning of transmitters or components.

### FEATURES:

- Interlock
- Quiet Operation
- Mounted on castors for ease of mobility

### OPTIONS:

- Internal or remote load operation
- Calorimetry
- 50 Hz operation

### SPECIFICATIONS

POWER RATING (CONTINUOUS DUTY)	5 KW
FREQUENCY RANGE	DC to 800 MHz
IMPEDANCE	50 $\Omega$ nominal
VSWR	1.1:1 to 800 MHz
AC POWER REQUIRED	110 VAC, 60 Hz or 230 VAC, 50/60 Hz Single phase
INPUT CONNECTION	1-5/8", 3-1/8" EIA Standard (others available)
NOMINAL DIMENSIONS (INCLUDING CONNECTIONS)	71 cm x 50 cm x 51cm (28" x 19½" x 20")
NOMINAL WEIGHT	36 kilograms (80 lbs.)

### Model 5805



# ALTRONIC RESEARCH INC.

CALL TOLL FREE 1-800-482-LOAD

P.O. BOX 249, Yellville, AR 72687 (870) 449-4093

[www.altronic.com](http://www.altronic.com)

